



#### MS27468T15F15P Information

Heisener.com

Part Number MS27468T15F15P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 15POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MS27468T15F15P Specifications**

| Manufacturer Part NumberMS27468T15F15PManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Male PinsNumber of Positions15Shell Size - Insert15-15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A, 13AReport errors? |                          |  |
|--|--------------------------|--|
| Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 15 Shell Size - Insert 15-15 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.   | Manufacturer Part Number | MS27468T15F15P                         |
| Circular Connectors  Package - Series Military, MIL-DTL-38999 Series I  Connector Type Receptacle, Male Pins  Number of Positions 15 Shell Size - Insert 15-15 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A  | Manufacturer             | Amphenol Aerospace Operations          |
| Package - Military, MIL-DTL-38999 Series I  Connector Type Receptacle, Male Pins  Number of Positions 15  Shell Size - Insert 15-15  Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features - Voltage - Rated 600VAC, 850VDC  Current Rating 7   | Category                 | Connectors, Interconnects              |
| Series Military, MIL-DTL-38999 Series I  Connector Type Receptacle, Male Pins  Number of Positions 15  Shell Size - Insert 15-15  Shell Size, MIL  |                          | Circular Connectors                    |
| Connector TypeReceptacle, Male PinsNumber of Positions15Shell Size - Insert15-15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A, 13A   | Package                  | -                                      |
| Number of Positions15Shell Size - Insert15-15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A, 13A  | Series                   | Military, MIL-DTL-38999 Series I       |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A, 13A   | Connector Type           | Receptacle, Male Pins                  |
| Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A   | Number of Positions      | 15                                     |
| Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A, 13A   | Shell Size - Insert      | 15-15                                  |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A   | Shell Size, MIL          | -                                      |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A   | Mounting Type            | Panel Mount, Bulkhead - Front Side Nut |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A   | Termination              | Crimp                                  |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A  | Fastening Type           | Bayonet Lock                           |
| Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  Gold  -  7.5A, 13A  | Orientation              | N (Normal)                             |
| Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A   | Ingress Protection       | Environment Resistant                  |
| Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A   | Shell Material, Finish   | Aluminum, Nickel Plated, Electroless   |
| Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A  | Contact Finish           | Gold                                   |
| Current Rating 7.5A, 13A   | Features                 | -                                      |
|  | Voltage - Rated          | 600VAC, 850VDC                         |
| Report errors?   | Current Rating           | 7.5A, 13A                              |
|  |                          | Report errors?                         |

#### MS27468T15F15P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS27468T15F15P Payment Methods



















## MS27468T15F15P Shipping Methods













If you have any question about MS27468T15F15P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com