



MS27468T15F5S Information

Heisener.com

Part Number MS27468T15F5S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 5POS JAM NUT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27468T15F5S Specifications

Manufacturer Part Number MS27468T15F5S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 15-5 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert15-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Manufacturer Part Number	MS27468T15F5S
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert15-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert15-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 15-5 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert15-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Package	-
Number of Positions5Shell Size - Insert15-5Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Number of Positions	5
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Size - Insert	15-5
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold Gold 13A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	13A
		Report errors?

MS27468T15F5S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27468T15F5S Payment Methods





















MS27468T15F5S Shipping Methods













If you have any question about MS27468T15F5S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com