



### MS27472E16F26S Information

Heisener.com

Part Number MS27472E16F26S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 26POS WALL MT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS27472E16F26S Specifications

Manufacturer Part Number       MS27472E16F26S         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series II         Connector Type       Receptacle, Female Sockets         Number of Positions       26         Shell Size - Insert       16-26         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated, Electroless         Contact Finish       Gold         Features       -         Voltage - Rated       600VAC, 850VDC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets  Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Convert Rating 7.5A	Manufacturer Part Number	MS27472E16F26S
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Package	-
Number of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Features - Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Number of Positions	26
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Shell Size - Insert	16-26
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  Gold  - 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A
		Report errors?

#### MS27472E16F26S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **MS27472E16F26S Payment Methods**



















# MS27472E16F26S Shipping Methods













If you have any question about MS27472E16F26S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com