



#### MS27472E20F41S Information

Heisener.com

Part Number MS27472E20F41S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 41POS WALL MT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS27472E20F41S Specifications**

Manufacturer Part Number       MS27472E20F41S         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series II         Connector Type       Receptacle, Female Sockets         Number of Positions       41         Shell Size - Insert       20-41         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated, Electroless         Contact Finish       Gold         Features       -         Voltage - Rated       600VAC, 850VDC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 20-41 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Manufacturer Part Number	MS27472E20F41S
Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 20-41 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating  7.5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 41 Shell Size - Insert 20-41 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II  Connector Type Receptacle, Female Sockets  Number of Positions 41  Shell Size - Insert 20-41  Shell Size, MIL - Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features - Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A		Circular Connectors
Connector Type Receptacle, Female Sockets  Number of Positions 41  Shell Size - Insert 20-41  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features -  Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Package	-
Number of Positions  Shell Size - Insert  20-41  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Features  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Number of Positions	41
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold  Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size - Insert	20-41
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold  600VAC, 850VDC 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
-	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A
		Report errors?

#### MS27472E20F41S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MS27472E20F41S Payment Methods**



















# MS27472E20F41S Shipping Methods













If you have any question about MS27472E20F41S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com