



#### MS27473E20A2S Information

Heisener.com

Part Number MS27473E20A2S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 65POS STRAIGHT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS27473E20A2S Specifications

| Manufacturer Part Number       MS27473E20A2S         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series II         Connector Type       Plug, Female Sockets         Number of Positions       65         Shell Size - Insert       20-2         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Cadmium over Nickel Plated         Contact Finish       Gold         Features       -         Voltage - Rated       400VAC, 500VDC         Current Rating       5A  |                          |                                      |
|---|--------------------------|--------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Female SocketsNumber of Positions65Shell Size - Insert20-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Manufacturer Part Number | MS27473E20A2S                        |
| Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Female SocketsNumber of Positions65Shell Size - Insert20-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A  | Manufacturer             | Amphenol Aerospace Operations        |
| Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Female SocketsNumber of Positions65Shell Size - Insert20-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A  | Category                 | Connectors, Interconnects            |
| Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Female Sockets  Number of Positions 65  Shell Size - Insert 20-2  Shell Size, MIL  |                          | Circular Connectors                  |
| Connector TypePlug, Female SocketsNumber of Positions65Shell Size - Insert20-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Package                  | -                                    |
| Number of Positions65Shell Size - Insert20-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Series                   | Military, MIL-DTL-38999 Series II    |
| Shell Size - Insert 20-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A  | Connector Type           | Plug, Female Sockets                 |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Features - Voltage - Rated 400VAC, 500VDC  Current Rating  5A   | Number of Positions      | 65                                   |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Shell Size - Insert      | 20-2                                 |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Shell Size, MIL          | -                                    |
| Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 500VDC  Current Rating  5A   | Mounting Type            | Free Hanging (In-Line)               |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Termination              | Crimp                                |
| Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features -  Voltage - Rated 400VAC, 500VDC  Current Rating 5A   | Fastening Type           | Bayonet Lock                         |
| Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  - Sold  - Sold | Orientation              | N (Normal)                           |
| Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Ingress Protection       | Environment Resistant                |
| Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Shell Material, Finish   | Aluminum, Cadmium over Nickel Plated |
| Voltage - Rated 400VAC, 500VDC Current Rating 5A  | Contact Finish           | Gold                                 |
| Current Rating 5A   | Features                 | -                                    |
|   | Voltage - Rated          | 400VAC, 500VDC                       |
| Report errors?  | Current Rating           | 5A                                   |
|   |                          | Report errors?                       |

### MS27473E20A2S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MS27473E20A2S Payment Methods**





















### MS27473E20A2S Shipping Methods













If you have any question about MS27473E20A2S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com