



#### MS27473E24A2PB Information

Heisener.com

Part Number MS27473E24A2PB

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 100POS STRAIGHT W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS27473E24A2PB Specifications**

Manufacturer Part Number       MS27473E24A2PB         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series II         Connector Type       Plug, Male Pins         Number of Positions       100         Shell Size - Insert       24-2         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       B         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Cadmium over Nickel Plated         Contact Finish       Gold         Features       -         Voltage - Rated       400VAC, 500VDC         Current Rating       5A		
Category Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Male Pins  Number of Positions 100  Shell Size - Insert 24-2  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC  Current Rating  5A	Manufacturer Part Number	MS27473E24A2PB
Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Male Pins  Number of Positions 100  Shell Size - Insert 24-2  Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation B  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features - Voltage - Rated 400VAC, 500VDC  Current Rating 5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 100 Shell Size - Insert 24-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Male Pins  Number of Positions 100  Shell Size - Insert 24-2  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation B  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features -  Voltage - Rated 400VAC, 500VDC  Current Rating 5A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions100Shell Size - Insert24-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions  Shell Size - Insert  24-2  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  B  Ingress Protection  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Features  -  Voltage - Rated  400VAC, 500VDC  Current Rating  5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  B  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Features  Voltage - Rated  400VAC, 500VDC  Current Rating  5A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating 5A	Number of Positions	100
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation B  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features -  Voltage - Rated 400VAC, 500VDC  Current Rating 5A	Shell Size - Insert	24-2
Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  B  Ingress Protection  Shell Material, Finish  Contact Finish  Features  Voltage - Rated  Current Rating  Bayonet Lock  B  Bayonet Lock  B  B  Bayonet Lock  B  B  Contact Finish  Contact Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Cold  Fourier Shell Material, Finish  Fourier Shell Material, Finish  Cold  Fourier Shell Material, Finish  Fourier Shell	Mounting Type	Free Hanging (In-Line)
Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  Voltage - Rated  400VAC, 500VDC  Current Rating  5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  400VAC, 500VDC  5A	Orientation	В
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	-
-	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

#### MS27473E24A2PB Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS27473E24A2PB Payment Methods





















### MS27473E24A2PB Shipping Methods













If you have any question about MS27473E24A2PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com