



#### MS27473E24A2S Information

Heisener.com

Part Number MS27473E24A2S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 100POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS27473E24A2S Specifications

| Manufacturer Part Number     MS27473E24A2S       Manufacturer     Amphenol Aerospace Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series II       Connector Type     Plug, Female Sockets       Number of Positions     100       Shell Size - Insert     24-2       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Cadmium over Nickel Plated       Contact Finish     Gold       Features     -       Voltage - Rated     400VAC, 500VDC       Current Rating     5A |                          |                                      |
|---|--------------------------|--------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Female SocketsNumber of Positions100Shell Size - Insert24-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A  | Manufacturer Part Number | MS27473E24A2S                        |
| Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Female SocketsNumber of Positions100Shell Size - Insert24-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Manufacturer             | Amphenol Aerospace Operations        |
| Package - Military, MIL-DTL-38999 Series II  Connector Type Plug, Female Sockets  Number of Positions 100  Shell Size - Insert 24-2  Shell Size, MIL - Crimp  Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features - Woltage - Rated 400VAC, 500VDC  Current Rating 5   | Category                 | Connectors, Interconnects            |
| Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Female Sockets  Number of Positions 100  Shell Size - Insert 24-2  Shell Size, MIL   |                          | Circular Connectors                  |
| Connector TypePlug, Female SocketsNumber of Positions100Shell Size - Insert24-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A  | Package                  | -                                    |
| Number of Positions100Shell Size - Insert24-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A  | Series                   | Military, MIL-DTL-38999 Series II    |
| Shell Size - Insert 24-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A  | Connector Type           | Plug, Female Sockets                 |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Features - Voltage - Rated 400VAC, 500VDC  Current Rating  5A   | Number of Positions      | 100                                  |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A   | Shell Size - Insert      | 24-2                                 |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Shell Size, MIL          | -                                    |
| Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 500VDC  Current Rating  5A   | Mounting Type            | Free Hanging (In-Line)               |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Termination              | Crimp                                |
| Ingress Protection  Environment Resistant  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 500VDC  Current Rating  5A   | Fastening Type           | Bayonet Lock                         |
| Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  - 5A   | Orientation              | N (Normal)                           |
| Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Ingress Protection       | Environment Resistant                |
| Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A   | Shell Material, Finish   | Aluminum, Cadmium over Nickel Plated |
| Voltage - Rated 400VAC, 500VDC Current Rating 5A  | Contact Finish           | Gold                                 |
| Current Rating 5A   | Features                 | -                                    |
|   | Voltage - Rated          | 400VAC, 500VDC                       |
| Report errors?  | Current Rating           | 5A                                   |
|   |                          | Report errors?                       |

### MS27473E24A2S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MS27473E24A2S Payment Methods**





















### MS27473E24A2S Shipping Methods













If you have any question about MS27473E24A2S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com