



MS27473T20A35PB Information

Heisener.com

Part Number MS27473T20A35PB

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 79POS STRAIGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27473T20A35PB Specifications

Manufacturer Part NumberMS27473T20A35PBManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Male PinsNumber of Positions79Shell Size - Insert20-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 79 Shell Size - Insert 20-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Be Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating Fastening Connectors Military, MIL-DTL-38999 Series II Connector Survey II Connector Type Plug, Male Pins Plug, Male Pins Plug, Male Pins II Connector Type Plug, Male Pins II Connector Type Plug, Male Pins II Connector Type Plug, Male Pins II Connector Survey II	Manufacturer Part Number	MS27473T20A35PB
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Male PinsNumber of Positions79Shell Size - Insert20-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Male PinsNumber of Positions79Shell Size - Insert20-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 79 Shell Size - Insert 20-35 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions79Shell Size - Insert20-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions79Shell Size - Insert20-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert 20-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Voltage - Rated 400VAC, 500VDC Current Rating Free Hanging (In-Line) Free Hanging (In-Line) Action Gold For Hanging (In-Line) Auminum Comp Bayonet Lock B Gold Environment Resistant Aluminum over Nickel Plated Contact Finish Features - Voltage - Rated 5A	Number of Positions	79
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Shell Size - Insert	20-35
Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold 400VAC, 500VDC 5A	Orientation	В
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	-
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

MS27473T20A35PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27473T20A35PB Payment Methods





















MS27473T20A35PB Shipping Methods













If you have any question about MS27473T20A35PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com