



MS27474E16B99P Information

Heisener.com

Part Number MS27474E16B99P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 23POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27474E16B99P Specifications

Manufacturer Part Number MS27474E16B99P Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 23 Shell Size - Insert 16-99 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 23 Shell Size - Insert 16-99 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7- Termination Circular Connectors Military, MIL-DTL-38999 Series II Receptacle, Male Pins Number of Position Receptacle, Male Pins Receptacle, Male Pins Number o	Manufacturer Part Number	MS27474E16B99P
Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 23 Shell Size - Insert 16-99 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7,5A, 13A	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 23 Shell Size - Insert 16-99 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Woltage - Rated 600VAC, 850VDC Current Rating 7 Type Military Military, Mili	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 23 Shell Size - Insert 16-99 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions23Shell Size - Insert16-99Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A, 13A	Package	-
Number of Positions23Shell Size - Insert16-99Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A, 13A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Number of Positions	23
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7,5A, 13A	Shell Size - Insert	16-99
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7,5A, 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A, 13A	Contact Finish	Gold
Current Rating 7.5A, 13A	Features	-
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A, 13A
The post of the second		Report errors?

MS27474E16B99P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27474E16B99P Payment Methods



















MS27474E16B99P Shipping Methods













If you have any question about MS27474E16B99P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com