



MS27474E22F2S Information

Heisener.com

Part Number MS27474E22F2S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 85POS JAM NUT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27474E22F2S Specifications

Manufacturer Part Number MS27474E22F2S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Manufacturer Part Number	MS27474E22F2S
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions85Shell Size - Insert22-2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Woltage - Rated 400VAC, 500VDC Current Rating 3A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions85Shell Size - Insert22-2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Package	-
Number of Positions85Shell Size - Insert22-2Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Voltage - Rated 400VAC, 500VDC Current Rating Aunum, Mickel Plated, Electroless 3A	Number of Positions	85
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Size - Insert	22-2
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold - 3A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 400VAC, 500VDC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	3A
		Report errors?

MS27474E22F2S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27474E22F2S Payment Methods



















MS27474E22F2S Shipping Methods













If you have any question about MS27474E22F2S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com