



MS27474E24F19S Information

Heisener.com

Part Number MS27474E24F19S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 19POS JAM NUT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27474E24F19S Specifications

Manufacturer Part Number MS27474E24F19S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated Connectors, Interconnects Circular Connectors Hilleronnects Connectors Interconnects Connectors Interconnectors Interconnects Interconnectors Interc	Manufacturer Part Number	MS27474E24F19S
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDC	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 19 Shell Size - Insert 24-19 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC	Package	-
Number of Positions19Shell Size - Insert24-19Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDC	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Voltage - Rated 600VAC, 850VDC	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Number of Positions	19
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Shell Size - Insert	24-19
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Aluminum, Nickel Plated, Electroless Gold 600VAC, 850VDC	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC, 850VDC	Contact Finish	Gold
	Features	-
Current Rating 23A	Voltage - Rated	600VAC, 850VDC
2017	Current Rating	23A
Report errors?		Report errors?

MS27474E24F19S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27474E24F19S Payment Methods





















MS27474E24F19S Shipping Methods













If you have any question about MS27474E24F19S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com