



MS27474T10A13P Information

Heisener.com

Part Number MS27474T10A13P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 13POS JAM NUT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27474T10A13P Specifications

Manufacturer MS27474T10A13P Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 10-13 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 10-13 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 7 Circular Connectors Military, MIL-DTL-38999 Series II Connector Sull Neceptacle, Male Pins Number of Position 10-13 Shell Material, Finish Panel Mount, Bulkhead - Front Side Nut Pennel	Manufacturer Part Number	MS27474T10A13P
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Male PinsNumber of Positions13Shell Size - Insert10-13Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 10-13 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Woltage - Rated 400VAC, 500VDC Current Rating 3	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 13 Shell Size - Insert 10-13 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions13Shell Size - Insert10-13Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Package	-
Number of Positions Shell Size - Insert 10-13 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Number of Positions	13
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Size - Insert	10-13
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold - 3A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 500VDC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	3A
		Report errors?

MS27474T10A13P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27474T10A13P Payment Methods



















MS27474T10A13P Shipping Methods













If you have any question about MS27474T10A13P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com