



MS27484E14F35SB Information

Heisener.com

Part Number MS27484E14F35SB

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 37POS STRAIGHT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27484E14F35SB Specifications

| Manufacturer Part Number MS27484E14F35SB Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Female Sockets Number of Positions 37 Shell Size - Insert 14-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A Report errors? | | |
|--|--------------------------|--------------------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Female Sockets Number of Positions 37 Shell Size - Insert 14-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Manufacturer Part Number | MS27484E14F35SB |
| Circular Connectors Package Series Military, MIL-DTL-38999 Series II Connector Type Plug, Female Sockets Number of Positions 37 Shell Size - Insert 14-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Manufacturer | Amphenol Aerospace Operations |
| Package - Military, MIL-DTL-38999 Series II Connector Type Plug, Female Sockets Number of Positions 37 Shell Size - Insert 14-35 Shell Size, MIL - Connector Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-38999 Series II Connector Type Plug, Female Sockets Number of Positions 37 Shell Size - Insert 14-35 Shell Size, MIL | | Circular Connectors |
| Connector Type Plug, Female Sockets Number of Positions 37 Shell Size - Insert 14-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Package | - |
| Number of Positions37Shell Size - Insert14-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A | Series | Military, MIL-DTL-38999 Series II |
| Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating | Connector Type | Plug, Female Sockets |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Number of Positions | 37 |
| Mounting Type Free Hanging (In-Line) Crimp Bayonet Lock Orientation B Ingress Protection Shell Material, Finish Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Environment Bayonet Lock Environment Resistant Aluminum, Nickel Plated, Electroless Gold Voltage - Rated 400VAC, 500VDC Current Rating | Shell Size - Insert | 14-35 |
| Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Size, MIL | - |
| Fastening Type Orientation B Ingress Protection Environment Resistant Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating Bayonet Lock B Bayonet Lock B B Contact Finish Environment Resistant Aluminum, Nickel Plated, Electroless Sold Food Shielded 400VAC, 500VDC | Mounting Type | Free Hanging (In-Line) |
| Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Termination | Crimp |
| Ingress Protection Environment Resistant Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Shell Material, Finish Aluminum, Nickel Plated, Electroless Aluminum, Nickel Plated, Electroless Sold Cold Sold Sold Sold Sold Sold Sold Sold S | Orientation | В |
| Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Ingress Protection | Environment Resistant |
| Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Material, Finish | Aluminum, Nickel Plated, Electroless |
| Voltage - Rated 400VAC, 500VDC Current Rating 5A | Contact Finish | Gold |
| Current Rating 5A | Features | Shielded |
| - | Voltage - Rated | 400VAC, 500VDC |
| Report errors? | Current Rating | 5A |
| | | Report errors? |

MS27484E14F35SB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27484E14F35SB Payment Methods



















MS27484E14F35SB Shipping Methods













If you have any question about MS27484E14F35SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com