



MS27484T22A2PC Information

Heisener.com

Part Number MS27484T22A2PC

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 85POS STRAIGHT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27484T22A2PC Specifications

Manufacturer Part Number MS27484T22A2PC Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 3A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating A Military, MIL-DTL-38999 Series II Connectors III Connector Type Plug, Male Pins Plug, Male Pins Plug, Male Pins Plug, Male Pins III Connector Type Plug, Male Pins II Co	Manufacturer Part Number	MS27484T22A2PC
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Male PinsNumber of Positions85Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating3A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Crimp Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating S	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions85Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating3A	Package	-
Number of Positions85Shell Size - Insert22-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating3A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Shielded Voltage - Rated A00VAC, 500VDC Current Rating 3A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating Audit Ingress Since Hanging (In-Line) Crimp Free Hanging (In-Line) Free Hanging (In-Line) Coil Audit Hanging Free Hanging (In-Line) Addit Hanging Free Hanging (In-Line) Free Hanging (In-Line) Addit Hanging Free Hanging (In-Line) Free Hanging (In-Line) Addit Hanging Free Hanging (In-Line) Addit Hanging Free Hanging (In-Line) Addit Hanging Free Hanging (In-Line) Free Hanging (In-Line) Addit Hanging Free Hanging (In-Line) Bayonet Lock Coriental Hanging Free Hanging (In-Line) Bayonet Lock Coriental Hanging Free Hanging (In-Line) Bayonet Lock Coriental Hanging Free Hanging (In-Line) Bayonet Lock C Addit Hanging Free Hanging (In-Line) Bayonet Lock Coriental Hanging Free Han	Number of Positions	85
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating3A	Shell Size - Insert	22-2
Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Size, MIL	-
Fastening Type Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating Bayonet Lock Contact Finish Contact Finish Aluminum, Cadmium over Nickel Plated Aluminum, Cadmium over Nickel Plated 3A	Mounting Type	Free Hanging (In-Line)
Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 3A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 3A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold Cold Shielded 400VAC, 500VDC 3A	Orientation	С
Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 3A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 500VDC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	Shielded
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	3A
		Report errors?

MS27484T22A2PC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27484T22A2PC Payment Methods



















MS27484T22A2PC Shipping Methods













If you have any question about MS27484T22A2PC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com