



### MS27484T8A35SA Information

Heisener.com

Part Number MS27484T8A35SA

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 6POS STRAIGHT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS27484T8A35SA Specifications

Manufacturer Part Number       MS27484T8A35SA         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-38999 Series II         Connector Type       Plug, Female Sockets         Number of Positions       6         Shell Size - Insert       8-35         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       A         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Cadmium over Nickel Plated         Contact Finish       Gold         Features       Shielded         Voltage - Rated       400VAC, 500VDC         Current Rating       5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating  5A	Manufacturer Part Number	MS27484T8A35SA
Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Female Sockets  Number of Positions 6 Shell Size - Insert 8-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating  5  Military, MIL-DTL-38999 Series II  Aluminum Cookets  Free Hanging (In-Line)  Free Hanging (In-Line)  Crimp  Fastening Type Bayonet Lock Orientation A Ingress Protection Shielded Voltage - Rated 400VAC, 500VDC Current Rating	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 8-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II  Connector Type Plug, Female Sockets  Number of Positions 6 Shell Size - Insert 8-35 Shell Size, MIL		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 6 Shell Size - Insert 8-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded  Voltage - Rated 400VAC, 500VDC Current Rating 5A	Package	-
Number of Positions6Shell Size - Insert8-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Crimp  Fastening Type  Bayonet Lock  Orientation  A  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  400VAC, 500VDC  Current Rating  5A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating  5A	Number of Positions	6
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation A  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features Shielded  Voltage - Rated 400VAC, 500VDC  Current Rating 5A	Shell Size - Insert	8-35
Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  400VAC, 500VDC  Current Rating  5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  Shielded  400VAC, 500VDC  5A	Orientation	A
Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated 400VAC, 500VDC  Current Rating 5A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

#### MS27484T8A35SA Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS27484T8A35SA Payment Methods



















# MS27484T8A35SA Shipping Methods













If you have any question about MS27484T8A35SA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com