



MS27496E25B35SC Information

Heisener.com

Part Number MS27496E25B35SC

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 128POS BOX MNT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27496E25B35SC Specifications

| Manufacturer Part Number MS27496E25B3SSC Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 25-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | | |
|--|--------------------------|-------------------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 25-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating Series - Connectors, Interconnects Circular Connectors Military, MIL-DTL-38999 Series I Receptacle, Female Sockets Military, MIL-DTL-38999 Series I Receptacle, Female Sockets Number of Positions I Seeptacle, Female Sockets Cornector Receptacle, Female Sockets Number of Positions I Seeptacle, Female Sockets Level Sockets Aluminum, Flange Cornectors Circular Connectors Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating | Manufacturer Part Number | MS27496E25B35SC |
| Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 25-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating Military, MIL-DTL-38999 Series I Receptacles - Voltage - Rated Amilitary, MIL-DTL-38999 Series I Receptacles - Series I Receptacle Sevies I Receptacle Sev | Manufacturer | Amphenol Aerospace Operations |
| Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 25-35 Shell Size, MIL | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Package | - |
| Number of Positions128Shell Size - Insert25-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Series | Military, MIL-DTL-38999 Series I |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Flange Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 400VAC, 500VDC Current Rating 5A | Number of Positions | 128 |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Shell Size - Insert | 25-35 |
| Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Mounting Type | Panel Mount, Flange |
| Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold | Orientation | C |
| Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Material, Finish | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 400VAC, 500VDC Current Rating 5A | Contact Finish | Gold |
| Current Rating 5A | Features | - |
| | Voltage - Rated | 400VAC, 500VDC |
| Report errors? | Current Rating | 5A |
| | | Report errors? |

MS27496E25B35SC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27496E25B35SC Payment Methods





















MS27496E25B35SC Shipping Methods













If you have any question about MS27496E25B35SC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com