



MS27497E12A98S Information

Heisener.com

Part Number MS27497E12A98S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 10POS WALL MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27497E12A98S Specifications

Manufacturer Part Number MS27497E12A98S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 12-98 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 12-98 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Manufacturer Part Number	MS27497E12A98S
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 12-98 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 12-98 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Package	-
Number of Positions10Shell Size - Insert12-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Number of Positions	10
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Shell Size - Insert	12-98
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold - 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A
		Report errors?

MS27497E12A98S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27497E12A98S Payment Methods





















MS27497E12A98S Shipping Methods













If you have any question about MS27497E12A98S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com