



MS27497E22B2SA Information

Heisener.com

Part Number MS27497E22B2SA

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 85POS WALL MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27497E22B2SA Specifications

Manufacturer Part Number MS27497E22B2SA Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Manufacturer Part Number	MS27497E22B2SA
Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating A Military, MIL-DTL-38999 Series II Receptacles II Receptacle, Female Sockets II Aluminum, Flange II Aluminum, Olive Drab Cadmium Plated Contact Finish Sold II Contact Finish Aluminum, Olive Drab Cadmium Plated II Contact Finish Aluminum, Olive Drab Cadmium Plat	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 85 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Package	-
Number of Positions85Shell Size - Insert22-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating 3A	Number of Positions	85
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Shell Size - Insert	22-2
Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Size, MIL	-
Fastening Type Orientation A Ingress Protection Environment Resistant Shell Material, Finish Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating Bayonet Lock A A A 400VAC, 500VDC	Mounting Type	Panel Mount, Flange
Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold 400VAC, 500VDC 3A	Orientation	A
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 400VAC, 500VDC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	3A
		Report errors?

MS27497E22B2SA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27497E22B2SA Payment Methods



















MS27497E22B2SA Shipping Methods













If you have any question about MS27497E22B2SA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com