



MS27497E22B35PB Information

Heisener.com

Part Number MS27497E22B35PB

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 100POS WALL MNT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27497E22B35PB Specifications

| Manufacturer Part Number MS27497E22B35PB Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | | |
|--|--------------------------|-------------------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection BN Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Manufacturer Part Number | MS27497E22B35PB |
| Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating Military, MIL - Receptacle, Male Pins Military, MIL-DTL-38999 Series II Receptacle, Male Pins Ingo Becate Insert - 400VAC, 500VDC Current Rating Series II Aluminum, Olive Drab Cadmium Plated Contact Finish Features - 5A | Manufacturer | Amphenol Aerospace Operations |
| Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Male PinsNumber of Positions100Shell Size - Insert22-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Category | Connectors, Interconnects |
| Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL | | Circular Connectors |
| Connector TypeReceptacle, Male PinsNumber of Positions100Shell Size - Insert22-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Package | - |
| Number of Positions100Shell Size - Insert22-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Series | Military, MIL-DTL-38999 Series II |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Flange Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 400VAC, 500VDC Current Rating - | Number of Positions | 100 |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A | Shell Size - Insert | 22-35 |
| Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Size, MIL | - |
| Fastening Type Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Mounting Type | Panel Mount, Flange |
| Orientation B Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold - 5A | Orientation | В |
| Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A | Shell Material, Finish | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 400VAC, 500VDC Current Rating 5A | Contact Finish | Gold |
| Current Rating 5A | Features | - |
| | Voltage - Rated | 400VAC, 500VDC |
| Report errors? | Current Rating | 5A |
| | | Report errors? |

MS27497E22B35PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27497E22B35PB Payment Methods



















MS27497E22B35PB Shipping Methods













If you have any question about MS27497E22B35PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com