



### MS27497E8F6S Information

Heisener.com

Part Number MS27497E8F6S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 6POS WALL MNT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MS27497E8F6S Specifications**

Manufacturer Part NumberMS27497E8F6SManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert8-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3AReport errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 8-6 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating  3A	Manufacturer Part Number	MS27497E8F6S
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert8-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert 8-6 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II  Connector Type Receptacle, Female Sockets  Number of Positions 6 Shell Size - Insert 8-6 Shell Size, MIL Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating 3A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert8-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Package	-
Number of Positions6Shell Size - Insert8-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating3A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Number of Positions	6
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold  Features - Voltage - Rated 400VAC, 500VDC  Current Rating 3A	Shell Size - Insert	8-6
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 500VDC  Current Rating  3A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  Gold  - 3A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 3A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 400VAC, 500VDC Current Rating 3A	Contact Finish	Gold
Current Rating 3A	Features	-
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	3A
		Report errors?

#### MS27497E8F6S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS27497E8F6S Payment Methods



















# MS27497E8F6S Shipping Methods













If you have any question about MS27497E8F6S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com