



### MS27499E8A98P Information

Heisener.com

Part Number MS27499E8A98P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 3POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS27499E8A98P Specifications**

Manufacturer Part Number     MS27499E8A98P       Manufacturer     Amphenol Aerospace Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series II       Connector Type     Receptacle, Male Pins       Number of Positions     3       Shell Size - Insert     8-98       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Cadmium over Nickel Plated       Contact Finish     Gold       Features     -       Voltage - Rated     600VAC, 850VDC       Current Rating     7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7  Circular Connectors Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Nell Pins II Series II S	Manufacturer Part Number	MS27499E8A98P
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 8-98 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II  Connector Type Receptacle, Male Pins  Number of Positions 3  Shell Size - Insert 8-98  Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Package	-
Number of Positions3Shell Size - Insert8-98Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Features - Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Number of Positions	3
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating7.5A	Shell Size - Insert	8-98
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC, 850VDC  Current Rating  7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features -  Voltage - Rated 600VAC, 850VDC  Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  - 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 600VAC, 850VDC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	7.5A
		Report errors?

### MS27499E8A98P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS27499E8A98P Payment Methods



















# MS27499E8A98P Shipping Methods













If you have any question about MS27499E8A98P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com