



MS27505E17A6P Information

Heisener.com

Part Number MS27505E17A6P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 6POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27505E17A6P Specifications

Manufacturer Part Number MS27505E17A6P Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A		
Category Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated Courrent Rating 23A	Manufacturer Part Number	MS27505E17A6P
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert17-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating23A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 17-6 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert17-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating23A	Package	-
Number of Positions6Shell Size - Insert17-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating23A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC Current Rating 17-6 Panel Mount, Flange - Rating	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC Current Rating 23A	Number of Positions	6
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A	Shell Size - Insert	17-6
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated Current Rating Environment Resistant Aluminum, Cadmium over Nickel Plated Gold Cold Current Rating	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating 23A	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 600VAC, 850VDC Current Rating 23A	Contact Finish	Gold
Current Rating 23A	Features	-
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	23A
		Report errors?

MS27505E17A6P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27505E17A6P Payment Methods



















MS27505E17A6P Shipping Methods













If you have any question about MS27505E17A6P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com