



### MS27513E16F8P Information

Heisener.com

Part Number MS27513E16F8P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 8POS BOX MNT W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS27513E16F8P Specifications

Manufacturer Part Number  Manufacturer  Amphenol Aerospace Operations  Category  Connectors, Interconnects  Circular Connectors  Package  - Series  Military, MIL-DTL-38999 Series II  Connector Type  Receptacle, Male Pins  Number of Positions  8 Shell Size - Insert  16-8 Shell Size, MIL  - Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  - Voltage - Rated  900VAC, 1250VDC  Current Rating  Ingress Perton Series II  Amphenol Aerospace Operations  Miscrepace Operations  Military, Interconnects  Connectors  Amphenol Aerospace Operations  Amphenol Aerospace Operations  Illeronnectors  Circular Connectors  Amphenol Aerospace Operations  Features  Amphenol Aerospace Operations  Connectors  Interconnects  Connectors  Amphenol Aerospace Operations  Amphenol Aerospace Operations  Circular Connectors  Amphenol Aerospace Operations  Illeronnectors  Amphenol Aerospace Operations  Illeronnectors  Amphenol Aerospace Operations  Illeronnectors  Illeronnectors  Amphenol Aerospace Operations  Illeronnectors  Illeronnectors  Illeronnectors  Amphenol Aerospace Operations  Illeronnectors  Il		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Manufacturer Part Number	MS27513E16F8P
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Package	-
Number of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Shell Size - Insert	16-8
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  Gold  - 13A	Orientation	N (Normal)
Contact Finish Gold  Features - Voltage - Rated 900VAC, 1250VDC  Current Rating 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	-
•	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	13A
		Report errors?

#### MS27513E16F8P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS27513E16F8P Payment Methods



















### MS27513E16F8P Shipping Methods













If you have any question about MS27513E16F8P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com