



MS27656E15F35PD Information

Heisener.com

Part Number MS27656E15F35PD

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 37POS WALL MNT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27656E15F35PD Specifications

Manufacturer Part Number MS27656E15F35PD Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 37 Shell Size - Insert 15-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 37 Shell Size - Insert 15-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating 5 Circular Connectors Military, MIL-DTL-38999 Series I Receptacle, Male Pins Appears Appears Insert	Manufacturer Part Number	MS27656E15F35PD
Package-SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Male PinsNumber of Positions37Shell Size - Insert15-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package - Military, MIL-DTL-38999 Series I Connector Type Receptacle, Male Pins Number of Positions 37 Shell Size - Insert 15-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-38999 Series IConnector TypeReceptacle, Male PinsNumber of Positions37Shell Size - Insert15-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions37Shell Size - Insert15-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions37Shell Size - Insert15-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series I
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 400VAC, 500VDC Current Rating	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Number of Positions	37
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 500VDCCurrent Rating5A	Shell Size - Insert	15-35
Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Panel Mount, Flange
Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold - Sold - Sold	Orientation	D
Contact Finish Gold Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	-
-	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

MS27656E15F35PD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27656E15F35PD Payment Methods



















MS27656E15F35PD Shipping Methods













If you have any question about MS27656E15F35PD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com