



MS3100A18-29S Information

Heisener.com

Part Number MS3100A18-29S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 5POS WALL MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3100A18-29S Specifications

Manufacturer Part Number MS3100A18-29S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 18-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 18-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated SouvAC, 700VDC Current Rating -	Manufacturer Part Number	MS3100A18-29S
Circular Connectors Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 18-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 18-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 18-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 18-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Package	-
Number of Positions5Shell Size - Insert18-29Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Series	MIL-5015 Type
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating - 18-29 Panel Mount, Flange Panel Mount, Flange Aluminum Flange Solder Cup Threaded N (Normal) Aluminum Alloy, Olive Drab Cadmium Plated Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	5
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	18-29
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating Threaded N (Normal) Aluminum Alloy, Olive Drab Cadmium Plated Silver - Voltage - Rated 500VAC, 700VDC -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating - Silver	Ingress Protection	-
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

MS3100A18-29S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3100A18-29S Payment Methods



















MS3100A18-29S Shipping Methods













If you have any question about MS3100A18-29S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com