



MS3100E16-10S Information

Heisener.com

Part Number MS3100E16-10S **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 3 POS WALL MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3100E16-10S Specifications

Manufacturer Part Number MS3100E16-10S Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 41A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated Convertible Aluminum Contact Finish Silver Features Cable Clamp Voltage - Rated	Manufacturer Part Number	MS3100E16-10S
Circular Connectors Package Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated Converse Military, MIL-DTL-5015, MS Receptacle, each of the service of the sockets Nilitary, MIL-DTL-5015, MS Receptacle, each of the sockets NIL-DTL-5015, MS Receptacle, each of the sockets Number of Positions Number of Posi	Manufacturer	ITT Cannon, LLC
Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Package	-
Number of Positions Shell Size - Insert 16-10 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 16-10 Local Size Panel Mount, Flange Panel Mount, Flange Threaded Solder Cup Threaded N (Normal) Environment Resistant Size Contact Finish Size Cable Clamp	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Number of Positions	3
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDC	Shell Size - Insert	16-10
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Cable Clamp Voltage - Rated Souvac, 700VDC	Orientation	N (Normal)
Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Ingress Protection	Environment Resistant
Features Cable Clamp Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	Cable Clamp
Current Rating 41A	Voltage - Rated	500VAC, 700VDC
	Current Rating	41A
Report errors?		Report errors?

MS3100E16-10S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3100E16-10S Payment Methods



















MS3100E16-10S Shipping Methods













If you have any question about MS3100E16-10S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com