

# MS3100E22-12P

#### MS3100E22-12P Information

Contraction the second	MS3100E22-12P Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN RCPT 5POS WALL MNT W/PINS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### MS3100E22-12P Specifications

ManufacturerAmphenol Industrial OperationsCategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-12Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionSilverShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedShell Size FasteningSilverFasteniesSilverContact FinishSilverFastensSilver <th></th> <th></th>		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Package-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	MS3100E22-12P
Circular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishStrian ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-12Shell Size, MIL-Mounting TypePanel Mount, FlangeMounting TypeSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverContact FinishSilverVoltage - RatedStrain ReliefVoltage - Rated-Current Rating-Current Rating-Strain Relief-Strain Relief-St	Category	Connectors, Interconnects
SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStrain ReliefVoltage - Rated-Current Rating-		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions5Shell Size - Insert22-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-	Series	MIL-5015 Type
Shell Size - Insert22-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Connector Type	Receptacle, Male Pins
Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesSrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Number of Positions	5
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	22-12
TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Mounting Type	Panel Mount, Flange
OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Termination	Solder Cup
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Orientation	N (Normal)
Contact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Ingress Protection	Environment Resistant
FeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated900VAC, 1250VDCCurrent Rating-	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

#### MS3100E22-12P Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MS3100E22-12P Payment Methods



# MS3100E22-12P Shipping Methods



If you have any question about MS3100E22-12P, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com