

# MS3100E22-19P

#### MS3100E22-19P Information

Heisener.com	 MS3100E22-19P Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN RCPT 14POS WALL MNT PIN - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## MS3100E22-19P Specifications

ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsConnectors, InterconnectsCircular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsConnector Type14Shell Size - Insert22-19Munting TypePanel Mount, FlangeForminationSolder CupForminationSolder CupFastening TypeThreadedShell Material, FinishEnvironment ResistantShell Material, FinishSilverContact FinishSilverFeaturesStain ReliefVoltage - RatedStorAC, 700VDC		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Package-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsConnector Type14Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangeFerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishStrian ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	MS3100E22-19P
Circular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangeFerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangeForminationSolder CupFastening TypeThreadedDrientationN(Normal)Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedShell Material, FinishSilverFeaturesStrian ReliefVoltage - RatedStoVAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMIL-5015 TypeConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangePorninationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangeForminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions14Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangeMounting TypeSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrin ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	MIL-5015 Type
Shell Size - Insert22-19Shell Size, MIL-Mounting TypePanel Mount, FlangeFerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishStrain ReliefFeaturesStovAC, 700VDCCurrent Rating-	Connector Type	Receptacle, Male Pins
Shell Size, MIL-Mounting TypePanel Mount, FlangeFerminationSolder CupFastening TypeThreadedOrientationN(Normal)OrientationEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Number of Positions	14
Mounting TypePanel Mount, FlangeFerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrian ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	22-19
TerminationSolder CupFastening TypeThreadedDrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size, MIL	-
Fastening TypeThreadedFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Mounting Type	Panel Mount, Flange
DrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Termination	Solder Cup
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Orientation	N (Normal)
Contact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Ingress Protection	Environment Resistant
FeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated500VAC, 700VDCCurrent Rating-	Contact Finish	Silver
Current Rating -	Features	Strain Relief
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

#### MS3100E22-19P Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3100E22-19P Payment Methods



### MS3100E22-19P Shipping Methods



If you have any question about MS3100E22-19P, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com