



MS3100R22-7P Information

Heisener.com

Part Number MS3100R22-7P **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 1POS WALL MNT W/PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3100R22-7P Specifications

Manufacturer Part Number MS3100R22-7P Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 1 Shell Size - Insert 22-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	-	
Category Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 1 Shell Size - Insert 22-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell Voltage - Rated Connectors Military, MIL-DTL-5015, MS Receptacle, Male Pins Nilitary, MIL-DTL-5015, MS Receptacle, Male Pins Neceptacle, Male Pins Nece	Manufacturer Part Number	MS3100R22-7P
Circular Connectors Package Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 1 Shell Size - Insert 22-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell Voltage - Rated Contact Fasted Contact Fasted Circular Connectors Military, MIL-DTL-5015, MS Receptacle Allulitary, Mill-DTL-5015, MS Receptacle Allulitary, Mill-DTL-5015, MS Receptacle Allulitary, Mill-DTL-5015, MS Receptacle Allulitary, Mill-DTL-5015, MS	Manufacturer	ITT Cannon, LLC
Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 1 Shell Size - Insert 22-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 1 Shell Size - Insert 22-7 Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 1 Shell Size - Insert 22-7 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	Package	-
Number of Positions Shell Size - Insert 22-7 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell Voltage - Rated 1250VAC, 1750VDC	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell Voltage - Rated 1250VAC, 1750VDC	Number of Positions	1
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshellVoltage - Rated1250VAC, 1750VDC	Shell Size - Insert	22-7
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Backshell Voltage - Rated Aluminum Alloy, Olive Drab Cadmium Plated Silver Backshell	Orientation	N (Normal)
Contact Finish Silver Features Backshell Voltage - Rated 1250VAC, 1750VDC	Ingress Protection	Environment Resistant
Features Backshell Voltage - Rated 1250VAC, 1750VDC	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 1250VAC, 1750VDC	Contact Finish	Silver
	Features	Backshell
0.00	Voltage - Rated	1250VAC, 1750VDC
Current Rating 245A	Current Rating	245A
Report errors?		Report errors?

MS3100R22-7P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3100R22-7P Payment Methods





















MS3100R22-7P Shipping Methods













If you have any question about MS3100R22-7P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com