



MS3100R24-12P Information

Heisener.com

Part Number MS3100R24-12P **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 5POS WALL MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3100R24-12P Specifications

Manufacturer Part Number MS3100R24-12P Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshellVoltage - Rated500VAC, 700VDCCurrent Rating41A, 135A	Manufacturer Part Number	MS3100R24-12P
Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert24-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshellVoltage - Rated500VAC, 700VDCCurrent Rating41A, 135A	Package	-
Number of Positions Shell Size - Insert 24-12 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Number of Positions	5
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Shell Size - Insert	24-12
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Backshell Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Backshell 41A, 135A	Orientation	N (Normal)
Contact Finish Silver Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Ingress Protection	Environment Resistant
Features Backshell Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 41A, 135A	Contact Finish	Silver
Current Rating 41A, 135A	Features	Backshell
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	41A, 135A
		Report errors?

MS3100R24-12P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3100R24-12P Payment Methods



















MS3100R24-12P Shipping Methods













If you have any question about MS3100R24-12P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com