

MS3101A28-6S

MS3101A28-6S Information

Heisener.com	 MS3101A28-6S Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN RCPT 3POS FREE HNG W/SCKT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MS3101A28-6S Specifications

Manufacturer Part Number MS3101A28-6S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 28-6 Mounting Type ree Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N(Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Features - Voltage - Rated 900VAC, 1250VDC		
CategoryCanactors, InterconnectsCategoryCircular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert28-6Munting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypeNicronalOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFortures-Solder CupSilverContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	MS3101A28-6S
Initial ConnectorsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCFurent Rating-	Manufacturer	Amphenol Industrial Operations
Package.SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL.Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientation.Ingress Protection.Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeatures.Voltage - Rated.Orientating.Store Trainsh.Store Trainsh.Store Trainsh.Contact Finish.Store Trainsh.Store Trainsh	Category	Connectors, Interconnects
SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluninum Alloy, Olive Drab Cadmium PlatedFoatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact Finish-Features-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	MIL-5015 Type
Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluninum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900YAC, 1250VDCCurrent Rating-	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedForientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	28-6
TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Termination	Solder Cup
Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Orientation	N (Normal)
Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Ingress Protection	-
Features-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated900VAC, 1250VDCCurrent Rating-	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors	Current Rating	-
		Report errors?

MS3101A28-6S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3101A28-6S Payment Methods



MS3101A28-6S Shipping Methods



If you have any question about MS3101A28-6S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com