



## MS3101E18-4S Information

Heisener.com

Part Number MS3101E18-4S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 4POS FREE HNG W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MS3101E18-4S Specifications**

| Manufacturer Part Number       MS3101E18-4S         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-5015 Type         Connector Type       Receptacle, Female Sockets         Number of Positions       4         Shell Size - Insert       18-4         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       900VAC, 1250VDC         Current Rating       -         Report errors?   | _                        |   |
|--|--------------------------|---|
| Category Connectors, Interconnects Circular Connectors  Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -  | Manufacturer Part Number | MS3101E18-4S                              |
| Circular Connectors  Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 18-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Onover the Author of the | Manufacturer             | Amphenol Industrial Operations            |
| Package - MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 18-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -  | Category                 | Connectors, Interconnects                 |
| Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 18-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -   |                          | Circular Connectors                       |
| Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert18-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-   | Package                  | -   |
| Number of Positions4Shell Size - Insert18-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-   | Series                   | MIL-5015 Type                             |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  -  | Connector Type           | Receptacle, Female Sockets                |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating  | Number of Positions      | 4   |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating-  | Shell Size - Insert      | 18-4                                      |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -  | Shell Size, MIL          | -   |
| Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -   | Mounting Type            | Free Hanging (In-Line)                    |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -   | Termination              | Solder Cup                                |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating -  | Fastening Type           | Threaded                                  |
| Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  -   | Orientation              | N (Normal)                                |
| Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  Silver  Strain Relief  | Ingress Protection       | Environment Resistant                     |
| Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating -  | Shell Material, Finish   | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 900VAC, 1250VDC Current Rating -   | Contact Finish           | Silver                                    |
| Current Rating -   | Features                 | Strain Relief                             |
| •  | Voltage - Rated          | 900VAC, 1250VDC                           |
| Report errors?   | Current Rating           | -   |
|  |                          | Report errors?                            |

#### MS3101E18-4S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3101E18-4S Payment Methods



















## **MS3101E18-4S Shipping Methods**













If you have any question about MS3101E18-4S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com