



MS3101F18-3P Information

Heisener.com

Part Number MS3101F18-3P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 2POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3101F18-3P Specifications

Manufacturer Part NumberMS3101F18-3PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert18-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment Resistant		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 18-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant	Manufacturer Part Number	MS3101F18-3P
Circular Connectors Package - Series Military, MIL-DTL-5015 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 18-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant	Manufacturer	Amphenol Industrial Operations
Package - Series Military, MIL-DTL-5015 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 18-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 18-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 18-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant	Package	-
Number of Positions2Shell Size - Insert18-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment Resistant	Series	Military, MIL-DTL-5015
Shell Size - Insert18-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment Resistant	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant	Number of Positions	2
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment Resistant	Shell Size - Insert	18-3
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant	Termination	Solder Cup
Ingress Protection Environment Resistant	Fastening Type	Threaded
	Orientation	N (Normal)
	Ingress Protection	Environment Resistant
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Contact Finish Silver	Contact Finish	Silver
Features Strain Relief	Features	Strain Relief
Voltage - Rated 900VAC, 1250VDC	Voltage - Rated	900VAC, 1250VDC
Current Rating -	Current Rating	-
Report errors?		Report errors?

MS3101F18-3P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3101F18-3P Payment Methods





















MS3101F18-3P Shipping Methods













If you have any question about MS3101F18-3P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com