



## MS3101F20-17P Information

Heisener.com

**Part Number** MS3101F20-17P **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 6 POS FREE HNG W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3101F20-17P Specifications

Manufacturer Part Number       MS3101F20-17P         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-5015, MS         Connector Type       Receptacle, Male Pins         Number of Positions       6         Shell Size - Insert       20-17         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Cable Clamp         Voltage - Rated       500VAC, 700VDC         Current Rating       22A, 41A         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 20-17 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated Current Rating 22A, 41A	Manufacturer Part Number	MS3101F20-17P
Circular Connectors  Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 20-17 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 20-17 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 2	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS  Connector Type Receptacle, Male Pins  Number of Positions 6  Shell Size - Insert 20-17  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert20-17Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Package	-
Number of Positions Shell Size - Insert 20-17 Shell Size, MIL  Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating  22A, 41A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Number of Positions	6
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A	Shell Size - Insert	20-17
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Cable Clamp  22A, 41A	Orientation	N (Normal)
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating Silver Cable Clamp 200VAC, 700VDC 22A, 41A	Ingress Protection	Environment Resistant
Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	Cable Clamp
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A, 41A
		Report errors?

### MS3101F20-17P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3101F20-17P Payment Methods





















## **MS3101F20-17P Shipping Methods**













If you have any question about MS3101F20-17P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com