

# MS3101R10SL-3PF16

## MS3101R10SL-3PF16 Information

Heisener.com

Part Number MS3101R10SL-3PF16
Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 3 POS FREE HNG W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS3101R10SL-3PF16 Specifications

Manufacturer Part Number       MS3101R10SL-3PF16         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-5015, MS         Connector Type       Receptacle, Male Pins         Number of Positions       3         Shell Size - Insert       10SL-3         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Backshell, Dust Cap         Voltage - Rated       500VAC, 700VDC         Current Rating       22A		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 10SL-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Backshell, Dust Cap Voltage - Rated Current Rating 22A	Manufacturer Part Number	MS3101R10SL-3PF16
Circular ConnectorsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions3Shell Size - Insert10SL-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesBackshell, Dust CapVoltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 10SL-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Dust Cap Voltage - Rated 500VAC, 700VDC Current Rating 2	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 3 Shell Size - Insert 10SL-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Dust Cap Voltage - Rated 500VAC, 700VDC Current Rating 22A		Circular Connectors
Connector Type Receptacle, Male Pins  Number of Positions 3  Shell Size - Insert 10SL-3  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Backshell, Dust Cap  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Package	-
Number of Positions  Shell Size - Insert  10SL-3  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Backshell, Dust Cap  Voltage - Rated  500VAC, 700VDC  Current Rating  22A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Backshell, Dust Cap  Voltage - Rated  500VAC, 700VDC  Current Rating  10SL-3	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Dust Cap  Voltage - Rated 500VAC, 700VDC Current Rating 22A	Number of Positions	3
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Backshell, Dust Cap  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Size - Insert	10SL-3
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Dust Cap Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Backshell, Dust Cap  Voltage - Rated  500VAC, 700VDC  Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Backshell, Dust Cap Voltage - Rated 500VAC, 700VDC Current Rating 22A	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Backshell, Dust Cap  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Backshell, Dust Cap  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Backshell, Dust Cap  22A	Orientation	N (Normal)
Contact Finish Silver  Features Backshell, Dust Cap  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Ingress Protection	Environment Resistant
Features Backshell, Dust Cap  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Backshell, Dust Cap
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A
		Report errors?

#### MS3101R10SL-3PF16 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3101R10SL-3PF16 Payment Methods



















## MS3101R10SL-3PF16 Shipping Methods













If you have any question about MS3101R10SL-3PF16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com