



## MS3102A18-22S Information

Heisener.com

Part Number MS3102A18-22S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 3POS BOX MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3102A18-22S Specifications

Manufacturer Part Number       MS3102A18-22S         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-5015 Type         Connector Type       Receptacle, Female Sockets         Number of Positions       3         Shell Size - Insert       18-22         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       -         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       900VAC, 1250VDC         Current Rating       -         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 18-22 Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer Part Number	MS3102A18-22S
Circular Connectors  Package - Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 18-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 18-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Woltage - Rated 900VAC, 1250VDC Current Rating	Category	Connectors, Interconnects
Series MIL-5015 Type Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 18-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -		Circular Connectors
Connector Type Receptacle, Female Sockets  Number of Positions 3  Shell Size - Insert 18-22  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Package	-
Number of Positions3Shell Size - Insert18-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	MIL-5015 Type
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	3
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features - Voltage - Rated 900VAC, 1250VDC  Current Rating -	Shell Size - Insert	18-22
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features - Voltage - Rated 900VAC, 1250VDC  Current Rating -	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features - Voltage - Rated 900VAC, 1250VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  Current Rating	Orientation	N (Normal)
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  Current Rating	Ingress Protection	-
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

#### MS3102A18-22S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3102A18-22S Payment Methods



















## MS3102A18-22S Shipping Methods













If you have any question about MS3102A18-22S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com