



MS3102A24-22P Information

Heisener.com

Part Number MS3102A24-22P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN RCPT 4POS BOX MNT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3102A24-22P Specifications

| Manufacturer Part Number MS3102A24-22P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - Report errors? | | |
|---|--------------------------|---|
| Category Circular Connectors Package - Series MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating - Cinnectors, Interconnects Circular Connectors AllL - OIL | Manufacturer Part Number | MS3102A24-22P |
| Circular Connectors Package - Series MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Manufacturer | Amphenol Industrial Operations |
| Package - MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - MIL - MIL-5015 Type HIL-5015 Type Paceptacle, Male Pins 4 Contact Finish Silver Features - Multinum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Multinum Alloy, Olive Drab Cadmium Plated Contact Finish Silver - Multinum Alloy Plated | Category | Connectors, Interconnects |
| Series MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | | Circular Connectors |
| Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Package | - |
| Number of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating- | Series | MIL-5015 Type |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Number of Positions | 4 |
| Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Shell Size - Insert | 24-22 |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Shell Size, MIL | - |
| Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Mounting Type | Panel Mount, Flange |
| Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Termination | Solder Cup |
| Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - Current Rating | Orientation | N (Normal) |
| Contact Finish Features Voltage - Rated Current Rating Silver - Current Rating | Ingress Protection | - |
| Features - Voltage - Rated 900VAC, 1250VDC Current Rating - | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 900VAC, 1250VDC Current Rating - | Contact Finish | Silver |
| Current Rating - | Features | - |
| - | Voltage - Rated | 900VAC, 1250VDC |
| Report errors? | Current Rating | - |
| | | Report errors? |

MS3102A24-22P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3102A24-22P Payment Methods



















MS3102A24-22P Shipping Methods













If you have any question about MS3102A24-22P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com