



# MS3102E14S-9P Information

Heisener.com

Part Number MS3102E14S-9P

Manufacturer Amphenol Industrial Operations

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 2POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3102E14S-9P Specifications

Manufacturer Part Number       MS3102E14S-9P         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-5015 Type         Connector Type       Receptacle, Male Pins         Number of Positions       2         Shell Size - Insert       14S-9         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       500VAC, 700VDC         Current Rating       -         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 14S-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating -	Manufacturer Part Number	MS3102E14S-9P
Circular Connectors  Package - Series MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 14S-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating -  Circular Connectors MIL-5015 Type Receptacle, Male Pins  14S-9 Panel Mount, Flange - Panel Mount, Flange Panel Mount, Flange Features Solder Cup Threaded - Voltage - Rated Solver - Current Rating	Manufacturer	Amphenol Industrial Operations
Package - MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 14S-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series MIL-5015 Type Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 14S-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert14S-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions2Shell Size - Insert14S-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Series	MIL-5015 Type
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  500VAC, 700VDC  Current Rating  -	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	14S-9
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - Current Rating	Orientation	N (Normal)
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  -  -  -  -  -  -  -  -  -  -  -  -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

### MS3102E14S-9P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3102E14S-9P Payment Methods



















### MS3102E14S-9P Shipping Methods













If you have any question about MS3102E14S-9P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com