



### MS3102E16-9P Information

Heisener.com

**Part Number** MS3102E16-9P **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 4 POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **MS3102E16-9P Specifications**

Manufacturer Part Number     MS3102E16-9P       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-5015, MS       Connector Type     Receptacle, Male Pins       Number of Positions     4       Shell Size - Insert     16-9       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Pating     22A 41A	WISSIUZEIU-SI Specifications	
Category         Connectors, Interconnects           Package         -           Series         Military, MIL-DTL-5015, MS           Connector Type         Receptacle, Male Pins           Number of Positions         4           Shell Size - Insert         16-9           Shell Size, MIL         -           Mounting Type         Panel Mount, Flange           Termination         Solder Cup           Fastening Type         Threaded           Orientation         N (Normal)           Ingress Protection         Environment Resistant           Shell Material, Finish         Aluminum Alloy, Olive Drab Cadmium Plated           Contact Finish         Silver           Features         -           Voltage - Rated         500VAC, 700VDC	Manufacturer Part Number	MS3102E16-9P
Circular Connectors  Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 16-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated  Convertified  Convertified  Convertified Converti	Manufacturer	ITT Cannon, LLC
Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 16-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert16-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC		Circular Connectors
Connector Type Receptacle, Male Pins  Number of Positions 4  Shell Size - Insert 16-9  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features  Voltage - Rated 500VAC, 700VDC	Package	-
Number of Positions  Shell Size - Insert  16-9  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  4  Convertible And	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  16-9  Annum Alloy  Longes  Panel Mount, Flange  Panel Mount, Flange  Panel Mount, Flange  Solder Cup  Threaded  N (Normal)  Aluminum Plated  Silver  -  Voltage - Rated	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC	Number of Positions	4
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Shell Size - Insert	16-9
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  -  Voltage - Rated  Threaded  N (Normal)  Environment Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  500VAC, 700VDC	Mounting Type	Panel Mount, Flange
Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	-
Current Rating 22A 41A	Voltage - Rated	500VAC, 700VDC
Current Nating 22A, 71A	Current Rating	22A, 41A
Report errors?		Report errors?

#### MS3102E16-9P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3102E16-9P Payment Methods



















## MS3102E16-9P Shipping Methods













If you have any question about MS3102E16-9P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com