



## MS3102E18-5S Information

Heisener.com

Part Number MS3102E18-5S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

**Description** CONN RCPT 3POS BOX MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MS3102E18-5S Specifications**

Manufacturer Part NumberMS3102E18-SSManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert18-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-Report errors?	•	
CategoryConnectors, InterconnectsPackage-SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert18-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	MS3102E18-5S
Package-SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert18-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert18-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMIL-5015 TypeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert18-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 18-5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - 900VAC, 1250VDC Current Rating	Package	-
Number of Positions3Shell Size - Insert18-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	MIL-5015 Type
Shell Size - Insert18-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 900VAC, 1250VDC  Current Rating -	Number of Positions	3
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	18-5
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - Current Rating	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Ourrent Rating - Silver	Ingress Protection	Environment Resistant
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

### MS3102E18-5S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3102E18-5S Payment Methods



















## MS3102E18-5S Shipping Methods













If you have any question about MS3102E18-5S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com