



### MS3102E28-20SY Information

Heisener.com

**Part Number** MS3102E28-20SY **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 14 POS BOX MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS3102E28-20SY Specifications

Manufacturer Part Number     MS3102E28-20SY       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     Military, MIL-DTL-5015, MS       Connector Type     Receptacle, Female Sockets       Number of Positions     14       Shell Size - Insert     28-20       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Solder Cup       Fastening Type     Threaded       Orientation     Y       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Rating     22A, 41A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Manufacturer Part Number	MS3102E28-20SY
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Manufacturer	ITT Cannon, LLC
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Package	-
Number of Positions14Shell Size - Insert28-20Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A	Number of Positions	14
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Shell Size - Insert	28-20
Termination Solder Cup Fastening Type Threaded Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Threaded Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Mounting Type	Panel Mount, Flange
Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A, 41A	Orientation	Y
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  22A, 41A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	-
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A, 41A
		Report errors?

#### MS3102E28-20SY Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3102E28-20SY Payment Methods



















## MS3102E28-20SY Shipping Methods













If you have any question about MS3102E28-20SY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com