



## MS3102R18-12PW Information

Heisener.com

**Part Number** MS3102R18-12PW **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN RCPT 6 POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3102R18-1	2PW	<b>Specifications</b>
M122107V10-1		Specifications

Manufacturer Part Number       MS3102R18-12PW         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-5015, MS         Connector Type       Receptacle, Male Pins         Number of Positions       6         Shell Size - Insert       18-12         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Solder Cup         Fastening Type       Threaded         Orientation       W         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       500VAC, 700VDC         Current Rating       22A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert18-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer Part Number	MS3102R18-12PW
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert18-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert18-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert18-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert18-12Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Package	-
Number of Positions Shell Size - Insert 18-12 Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Current Rating 22A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Number of Positions	6
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded  Orientation W  Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Size - Insert	18-12
Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Mounting Type	Panel Mount, Flange
Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Termination	Solder Cup
Ingress Protection  Environment Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Environment Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 22A	Orientation	W
Contact Finish Silver  Features - Voltage - Rated Current Rating  Silver  - 22A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A
		Report errors?

### MS3102R18-12PW Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3102R18-12PW Payment Methods



















# MS3102R18-12PW Shipping Methods













If you have any question about MS3102R18-12PW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com