



MS3102R18-9SZ Information

Heisener.com

Part Number MS3102R18-9SZ **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 7 POS BOX MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3102R18-9SZ Specifications

Manufacturer Part NumberMS3102R18-9SZManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A, 41AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Manufacturer Part Number	MS3102R18-9SZ
Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 18-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 200VAC, 250VDC Current Rating Z Connector Silver Connector Silver Connector Silver Circular Connectors Military, MIL-DTL-5015, MS Receptacle, Female Sockets 7 Shell Mount, Flange Panel Moun	Manufacturer	ITT Cannon, LLC
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 18-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Package	-
Number of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 18-9 Panel Mount, Flange Panel Mount, Flange Panel Mount, Flange Panel Mount, Flange Aluminum Flange Solder Cup Threaded Z Up Threaded 200VAC, 250VDC 22A, 41A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Number of Positions	7
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationZIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A, 41A	Shell Size - Insert	18-9
Termination Solder Cup Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Threaded Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Mounting Type	Panel Mount, Flange
Orientation Z Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Termination	Solder Cup
Ingress Protection Environment Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 200VAC, 250VDC 22A, 41A	Orientation	Z
Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	-
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	22A, 41A
		Report errors?

MS3102R18-9SZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3102R18-9SZ Payment Methods



















MS3102R18-9SZ Shipping Methods













If you have any question about MS3102R18-9SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com