



### MS3103-20-15P Information

Heisener.com

Part Number MS3103-20-15P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN RCPT 7POS BOX MNT PIN

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3103-20-15P Specifications

Manufacturer Part Number       MS3103-20-15P         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-5015         Connector Type       Receptacle, Male Pins         Number of Positions       7         Shell Size - Insert       20-15         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Potted         Voltage - Rated       500VAC, 700VDC         Current Rating       -         Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesPottedVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	MS3103-20-15P
Package-SeriesMilitary, MIL-DTL-5015Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesPottedVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMilitary, MIL-DTL-5015Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesPottedVoltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-5015Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesPottedVoltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesPottedVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesPottedVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	Military, MIL-DTL-5015
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Potted  Voltage - Rated 500VAC, 700VDC  Current Rating	Number of Positions	7
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesPottedVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	20-15
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Potted Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Potted Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Potted Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Potted  Voltage - Rated 500VAC, 700VDC  Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Potted  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Potted	Orientation	N (Normal)
Contact Finish Silver  Features Potted  Voltage - Rated Current Rating -	Ingress Protection	Environment Resistant
Features Potted  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Potted
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
*		Report errors?

### MS3103-20-15P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3103-20-15P Payment Methods



















### MS3103-20-15P Shipping Methods













If you have any question about MS3103-20-15P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com