



MS3106E16S-5S Information

Heisener.com

Part Number MS3106E16S-5S **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 3 POS STRAIGHT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3106E16S-5S Specifications

Manufacturer Part Number MS3106E16S-5S Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	•	
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated Current Rating 22A	Manufacturer Part Number	MS3106E16S-5S
Circular Connectors Package - Series Military, MIL-DTL-5015, MS Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 16S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert16S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating22A	Package	-
Number of Positions Shell Size - Insert 16S-5 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating22A	Shell Size - Insert	16S-5
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Fastening Type	Threaded
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Orientation	N (Normal)
Contact Finish Silver Cable Clamp, Coupling Nut Voltage - Rated Current Rating Silver Cable Clamp, Coupling Nut 500VAC, 700VDC	Ingress Protection	Environment Resistant
Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Cable Clamp, Coupling Nut
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A
		Report errors?

MS3106E16S-5S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3106E16S-5S Payment Methods



















MS3106E16S-5S Shipping Methods













If you have any question about MS3106E16S-5S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com