



MS3106E24-12P Information

Heisener.com

Part Number MS3106E24-12P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 5POS STRAIGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3106E24-12P Specifications

Manufacturer Part Number MS3106E24-12P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating - Connectors, Interconnects Circular Connectors MIL-5015 Type Plug, Male Pins Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Solder Cup Threaded Cup Threaded Solder Cup Threaded Threaded Orientation N (Normal) Festures - Voltage - Rated - Voltage - Rated - Current Rating -	Manufacturer Part Number	MS3106E24-12P
Circular Connectors Package - Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series MIL-5015 Type Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 24-12 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Package	-
Number of Positions Shell Size - Insert 24-12 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating -	Series	MIL-5015 Type
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	5
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	24-12
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - Current Rating	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating - Silver -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

MS3106E24-12P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3106E24-12P Payment Methods



















MS3106E24-12P Shipping Methods













If you have any question about MS3106E24-12P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com