

MS3106E24-16S

Quote

MS3106E24-16S Information

| Heisener.com | MS3106E24-16S Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN PLUG 7POS INLINE SKT - For the pricing/inventory/lead time, please contact | |
|--------------------|--|-----------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MS3106E24-16S Specifications

| Manufacturer Part Number MS3106E24-16S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Package - Series MIL-5015 Type Connector Type Plug, Female Sockets Number of Positions 7 Shell Size - Insert 24-16 Mounting Type Free Hanging (In-Line) Termination Solder Cup Packating Type Threaded Orientation N(Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Voltage - Rated - Voltage - Rated - | | |
|--|--------------------------|---|
| CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypePlug, Fenale SocketsNumber of Positions7Shell Size - Insert24-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesSilverVoltage - Rated-Cortert RatingSilverFeaturesSilverSolder CupSilverContact FinishSilverFeaturesSilverFeaturesSilverFeaturesSilverFortantionSilverFeaturesSilverFeatur | Manufacturer Part Number | MS3106E24-16S |
| PackageCircular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert24-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-Current Rating-Stateming Type- | Manufacturer | Amphenol Industrial Operations |
| Package-SeriesMIL-5015 TypeConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert24-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesSilverVoltage - RatedSina ReliefCurrent Rating-Current Rating-Solder Current Rating-Solder Rated-Solder Solder Sold | Category | Connectors, Interconnects |
| SeriesMIL-5015 TypeConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert24-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFoateresSilverFoateresStain ReliefVoltage - Rated-Current Rating-StateresStain Relief | | Circular Connectors |
| Connector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert24-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrian ReliefVoltage - Rated-Current Rating-Current Rating-Statemange- | Package | - |
| Number of Positions7Shell Size - Insert24-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrin ReliefVoltage - Rated-Current Rating-String Type-String Type- <td>Series</td> <td>MIL-5015 Type</td> | Series | MIL-5015 Type |
| Shell Size - Insert24-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-Strain Relief- | Connector Type | Plug, Female Sockets |
| Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluninum Alloy, Olive Drab Cadmium PlatedFeaturesSilverFotage - Rated-Voltage - Rated-Current Rating-Stant Reting- | Number of Positions | 7 |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedForientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating-Strain Rate- | Shell Size - Insert | 24-16 |
| TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating- | Shell Size, MIL | - |
| Fastening TypeThreadedFastening TypeN(Normal)OrientationN(Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating- | Mounting Type | Free Hanging (In-Line) |
| OrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating- | Termination | Solder Cup |
| Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating- | Fastening Type | Threaded |
| Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating- | Orientation | N (Normal) |
| Contact FinishSilverFeaturesStrain ReliefVoltage - Rated-Current Rating- | Ingress Protection | Environment Resistant |
| FeaturesStrain ReliefVoltage - Rated-Current Rating-Output-< | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated-Current Rating- | Contact Finish | Silver |
| Current Rating - | Features | Strain Relief |
| - | Voltage - Rated | - |
| Report error | Current Rating | - |
| | | Report errors? |

MS3106E24-16S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3106E24-16S Payment Methods



MS3106E24-16S Shipping Methods



If you have any question about MS3106E24-16S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com