



Heisener.com

### MS3106E24-7PWF187 Information

Part Number MS3106E24-7PWF187 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN PLUG 16POS CABLE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MS3106E24-7PWF187 Specifications

Manufacturer Part Number  Manufacturer  Category  Connectors, Interconnects  Circular Connectors  Package  Series  Military, MIL-DTL-5015, MS  Connector Type Plug, Male Pins  Number of Positions  16  Shell Size - Insert  24-7  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation W  Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp, Coupling Nut  Voltage - Rated Current Rating 22A, 41A  Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Male PinsNumber of Positions16Shell Size - Insert24-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Manufacturer Part Number	MS3106E24-7PWF187
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypePlug, Male PinsNumber of Positions16Shell Size - Insert24-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Plug, Male Pins Number of Positions 16 Shell Size - Insert 24-7 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 222, 41A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS  Connector Type Plug, Male Pins  Number of Positions 16  Shell Size - Insert 24-7  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation W  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp, Coupling Nut  Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions16Shell Size - Insert24-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationWIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable Clamp, Coupling NutVoltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Package	-
Number of Positions  Shell Size - Insert  24-7  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  W  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp, Coupling Nut  Voltage - Rated  500VAC, 700VDC  Current Rating  22A, 41A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Number of Positions	16
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation W  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp, Coupling Nut  Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A	Shell Size - Insert	24-7
Termination Solder Cup Fastening Type Threaded Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type  Orientation  W  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Cable Clamp, Coupling Nut  Voltage - Rated  500VAC, 700VDC  Current Rating  22A, 41A	Mounting Type	Free Hanging (In-Line)
Orientation W Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp, Coupling Nut Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Cable Clamp, Coupling Nut  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Cable Clamp, Coupling Nut  22A, 41A	Orientation	W
Contact Finish Silver Cable Clamp, Coupling Nut Voltage - Rated Current Rating 22A, 41A	Ingress Protection	Environment Resistant
Features Cable Clamp, Coupling Nut  Voltage - Rated 500VAC, 700VDC  Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Contact Finish	Silver
Current Rating 22A, 41A	Features	Cable Clamp, Coupling Nut
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A, 41A
1		Report errors?

#### MS3106E24-7PWF187 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MS3106E24-7PWF187 Payment Methods



















## MS3106E24-7PWF187 Shipping Methods













If you have any question about MS3106E24-7PWF187, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com