

MS3106E28-22PX

MS3106E28-22PX Information

Heisener.com Other service starts they	 MS3106E28-22PX Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN PLUG 6POS STRAIGHT W/PINS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MS3106E28-22PX Specifications

ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsConnectors, InterconnectsCircular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypePlug, Male PinsConnector Type6Shell Size - Insert28-22Shell Size, MIL-Munting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKaShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact Finish-Yotage - Rated900XC, 1250VDC		
CategoryConnectors, InterconnectsCircular ConnectorsPackagePackageSeriesMIL-5015 TypeConnector TypePlug, Male PinsConnector Type6Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact Finish-Voltage - Rated900VAC, 1250VDCCurrent Rating-Current Rating-	Manufacturer Part Number	MS3106E28-22PX
Circular ConnectorsPackage-SeriesMIL-5015 TypeConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact Finish-Voltage - Rated900VAC, 1250VDCCurrent Rating-Current Rating-Cu	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-5015 TypeConnector TypePlug, Male PinsConnector Type6Number of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeaturessilverFourge - Rated900VAC, 1250VDCCurrent Rating-Current Rating-	Category	Connectors, Interconnects
SeriesMIL-5015 TypeConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupTerminationSolder CupPastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFoatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	MIL-5015 Type
Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Connector Type	Plug, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationXOrientationEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	28-22
TerminationSolder CupFastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size, MIL	-
Fastening TypeThreadedOrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Mounting Type	Free Hanging (In-Line)
OrientationXIngress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Termination	Solder Cup
Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Orientation	X
Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Ingress Protection	Environment Resistant
Features-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated900VAC, 1250VDCCurrent Rating-	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

MS3106E28-22PX Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3106E28-22PX Payment Methods





If you have any question about MS3106E28-22PX, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com