



MS3106F16-10P Information

Heisener.com

Part Number MS3106F16-10P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN PLUG 3POS STRAIGHT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS3106F16-10P Specifications

Manufacturer Part NumberMS3106F16-10PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Wission 10-101 Specifications	
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDC	Manufacturer Part Number	MS3106F16-10P
Package-SeriesMilitary, MIL-DTL-5015Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDC	Manufacturer	Amphenol Industrial Operations
Package - Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015 Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDC	Package	-
Number of Positions Shell Size - Insert 16-10 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Senvironment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated SouvAC, 700VDC	Series	Military, MIL-DTL-5015
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 16-10 Lenvironment Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Solder Cup Threaded Aluminum Alloy Solder Cup Strain Relief Solver Strain Relief	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDC	Shell Size - Insert	16-10
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Threaded N (Normal) Surver Serving Plated Silver Solver Solver Strain Relief	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC	Ingress Protection	Environment Resistant
Features Strain Relief Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	Strain Relief
Current Rating -	Voltage - Rated	500VAC, 700VDC
	Current Rating	-
Report errors?		Report errors?

MS3106F16-10P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS3106F16-10P Payment Methods





















MS3106F16-10P Shipping Methods













If you have any question about MS3106F16-10P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com